

Split-Air Conditioner YPL 9002

Art.-No.: 23.651.68

Bar code: 4006825514933

Sales unit: 1 pc

One area – Split-Air Conditioner for wall installation with the functions: Cooling, heating, dehumidifying, time programming device for ON/OFF.

Complete with remote control and 4 m cooling agent connecting tubes with flexible insulation (max. 10 m possible at professional installation).

Easy installation of the air conditioner with a **cooling capacity of 2,500 W**. Ideal for rooms until approx. 80 m³. The unit consists of 2 parts, an outdoor part and one for indoors, in order to allow quick cooling and warrant an optimal noise level.

Fan speed with a maximum speed of 420 m³/h.

With the **automatic dehumidification** the units evaporates from its surrounding max. **1,0 l/h** of excess humidity.

Timer for programme settings, Automatic- and night functions.

All functions can be set with the **remote control**. Supplied with LCD indicator. Motorized ventilation lamella in the indoor unit.

Dimensions:

Indoor unit (WxHxD): 710x180x250 mm
Outdoor unit (WxHxD): 720x260x430 mm

Weight:

Indoor unit: 11 kg
Outdoor unit: 27 kg

Packing dimensions indoor unit: 750x260x320 mm
Packing dimensions outdoor unit: 765x350x500 mm

Features:

- LED display (1)
- Air escape lamella (2)
- Air suction grid (3)
- Remote control (4)
- Fan (5)
- Pipe connection

Technical data:

- | | |
|---------------------------------------|---|
| - Coolant_ | R407C |
| - Energy-Efficiency-Class: | D |
| - EER / COP: | 2.62 / - |
| - Energy consumption at cooling: | 480 kWh / Year |
| - Cooling capacity (ISO 5151): | 2,500 W |
| - Air throughput: | 420 m ³ /h |
| - Capacity of humidity reduction max: | 1.0 l/h |
| - Mains: | 220 - 240 V ~ 50 Hz |
| - Power: | 1,150 W |
| - Refrigerant quantity: | 500 g for 4 m pipe |
| - Noise level: | Indoors: ≤ 37 dB (A)
Outdoors: ≤ 52 dB (A) |

