

## Air Conditioner MKA 2800 E

Art.-No.: 23.603.15

Bar code: 4006825541144

Sales unit: 1 pc

Mobile and compact air conditioner, which provides a comfortable indoor climate. Cooling and dehumidifying in one unit. The unit is completely assembled and ready for service after the exhaust hose has been connected. With soft keys and the remote control all operating levels can be set and also the air conditioner can be switched on/off. The thermostat regulation provides a well-balanced indoor climate. This model is suitable for rooms of max. 75 m<sup>3</sup> volume.

### Features:

- Large control panel (1)
- Air discharge opening lamellas are adjustable (2) mechanically in vertical position
- 4 pcs castors (3)
- Exhaust air hose with adaptor (Ø 120 mm / L max. 150 cm) (4)
- Air suction filter with activated carbon filter (5)
- Remote control (6)
- Condensate return in the cooling operation – no condensate box emptying necessary
- Integrated condensate water box (approx. 1.2 l capacity)
- Constant drainage possible because of condensate water hose

### Functions:

- LED-Display
- Temperature level: +18° C up to +32° C
- Fan speed: 2-settings
- Operating level section (Mode): Autom., cooling, fan
- Power on-time: 1 to 12 h; Continuous operation
- Unit ON-OFF

### Technical data:

- Free of FCKW (R410A)
- Energy-Efficiency-Class: C
- EER / COP: 2.57 / -
- Energy consump. when cooling: 533 kWh per year
- Mains: 230 V ~ 50 Hz
- Cooling capacity: 2,740 watts / 9,350 BTU/h
- Air circulation max.: 350 m<sup>3</sup>/h
- Exhausted room humidity max. (30° C / 80% RH): approx. 36 l a day
- Quantity of coolant: 530 g
- Noise level: ≤ 56 dB (A)
- Housing dimensions H x W x D: 753 x 430 x 403 mm
- Packing dimensions H x W x D: 790 x 480 x 465 mm
- Unit Weight approx.: 30 kg
- Weight complete approx.: 32.5 kg

### Characteristics according to active standard EN 14511

### LED-Display for:

- Temperature (7)
- Timer ON (8)
- Automatic, cooling, fan (9)
- Fan speed (10)
- Compressor running (11)

