

Air Conditioner MKA 3002 M

Art.-No.: 23.603.10

Bar code: 4006825534016

Sales unit: 1 pc

Mobile and compact air conditioner, which provides a comfortable indoor climate in living quarters and workshops or offices at any time. Cooling and dehumidifying in one unit. The unit is completely assembled and ready for service after the exhaust hose has been connected.

All operating levels can be set with mechanical rotation switches and also the air conditioner can be switched on/off. The thermostat regulation provides a well-balanced indoor climate. This model is suitable for rooms of max. 65 m³ volume.

Features:

- Large control panel (1)
- Air discharge opening lamellas are adjustable mechanically in vertical and horizontal position (2)
- 4 pcs castors (3)
- Exhaust air hose with adapter (length max. 150 cm) (4)
- Air suction filter with activated carbon filter (5)
- Condensate return in the cooling operation – no condensate box emptying necessary
- Integrated condense water box (approx. 1.2 litre capacity)
- Constant drainage possible because of condensewaterhose

LED-Display (9) for:

- ON
- Fan running
- Cooling
- Water tank "full"

Functions:

- Power on-time: 1 to 8 h (6), Continuous operation
- Temperature level: +18°C up to +32°C (7)
- Fan speed: (Low Fan, High Fan, Low Cool, High Cool) (8)

Technical data:

- Coolant: R410A
- Energy-Efficiency-Class: B
- EER / COP: 2.84 / -
- Energy consump. when cool.: 417 kWh per year
- Mains: 230 V ~ 50 Hz
- Cooling capacity: 2366 watts
- Air circulation max.: 350 m³/h
- Exhausted room humidity max. (30°C / 80% RH) approx. 48 l a day
- Quantity of coolant: 540 g
- Noise level: ≤ 57 dB (A)
- Housing dimensions H x W x D: 750 x 400 x 380 mm
- Packing dimensions H x W x D: 780 x 460 x 450 mm
- Unit Weight: approx. 30 kg
- Weight complete: approx. 33 kg

Characteristics according to active standard EN 14511

