

Heating Generator HGG 110 Niro; Ex

Art.-No.: 23.301.31

Bar code: 4006825512809

Sales unit: 1 pc

Due to the high efficiency design and construction of the unit it could be kept small and handy with a high output. The normal connection is to a 5 resp. 11 kg propane/butane gas bottle. The integrated Piezo ignition as well as the thermal cut-out against over heating cut off the gas and warrant a safe operation.) A gas hose and the pressure reducer is not supplied.

Features:

- ON/OFF-switch for fan (1)
- gas valve button
- heating reflector made of galvanized sheet steel (2)
- housing made of stainless steel (3)
- carrying handle (4)
- Piezo ignition
- Back-fire safety device
- Piezo electrical flame safety
- Solenoid valve
- Mains cable

Technical data:

- | | |
|-------------------------------|------------------------|
| - Mains: | 230 V ~ 50 Hz, 38 W |
| - Nominal heat load: | 11,2 KW |
| - Nominal air volume: | 500 m ³ /h |
| - Nominal gas consumption: | 815 g/h liquid gas P/B |
| - Operating pressure: | 300 mbar |
| - Type of gas propane/butane: | class I.3 |
| - Weight: | 5,7 kg |
| - Packing dimensions: | 400 x 230 x 310 mm |



Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved

File: G:\Webshop\T-Produktbeschreibung\60\Originale_Englisch_PA04\2330131_01015.doc

Erstelldatum / create date: 14.07.2005 14:34

Aktualisiert / up dated: 21.07.2005