



Submersible Pump MSMP 750-S

Art.-No.: **41.705.87**

bar code: 4006825510188

sales unit: 4 pcs

Powerful and robust submersible pump to empty garden ponds, flooded basements and construction sites. It takes foreign particles up to Ø 35 mm in size. The pump is equipped with a float switch for automatic ON/OFF operation for a varying water level.

High quality standard at materials and constructional design, e. g. a stainless high-grade steel drive shaft warrants a maintenance-free operation and durable application.

Technical data:

- Mains:	230V ~ 50 Hz
- Power:	750 watts
- Delivery capacity max.:	15.000 l/h
- Delivery height max.:	8 m
- Immersion depth max.:	8 m
- Water temperature max.:	35°C
- Hose connection:	1 ½ " female thread
- Foreign particles size:	Ø 35 mm
- Mains cable:	10 m H05RN-F
- ON function:	approx. 50 cm
- OFF function:	approx. 5 cm
- Minimum immersion:	approx. 40 mm
- Weight:	6.1 kg
- Packing dimensions:	220 x 160 x 360 mm

Features:

- Carrying handle (1)
- Universal connection for 1" and 5/4" hose connection as well as 1" male thread (2)
- 90 ° angle bracket with 1 ½" x 1 ½" male thread (3)
- Float switch (4)

Performance data:

Delivery height:	Delivery capacity:
2 m	max. 13.000 l/h
4 m	max. 9.800 l/h
6 m	max. 5.300 l/h



As special accessory available:

Drainage hose 10 m / 1" (material: PVC)

Art.-No.: **41.737.11**

bar code: 4006825414707

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved

File: G:\Webshop\T-Produktbeschreibung\60\Originale_Englisch_PA04\4170587_01015.doc

Erstelldatum / create date: 25.05.2005 10:46

Aktualisiert / up dated: 13.06.2005