

### Features

- Powder-coated sawing table approx. 638 x 430 mm
- Powder-coated bench width extension approx. 638 x 250mm
- Powder-coated bench length extension approx. 430 x 320 mm
- Complete with base frame
- Parallel stop with 2 stop heights
- Cross fence tiltable from -45° to +45°
- Saw blade can be set from 0° to 45°
- Max. cutting height 80 mm
- Connection for dust extraction
- Waste bag for wood residues

### Technical Data

- Mains supply	230-240 V   50 Hz
- Max. power (S6   S6%)	2000 W   40 %
- Idle speed	4250 min <sup>-1</sup>
- Saw blade	Ø254 x ø30 mm
- Number of saw teeth	24 / 48 Pieces
- Swiveling range of saw blade	45 °
- Max. cutting height at 45°	55 mm
- Max. cutting height at 90°	80 mm
- Height adjustment continuous	0-80 mm
- Diameter of suction adapter	35 mm
- Working height	870 mm
- Size of working table	638 x 430 mm
- Table broadening left	638 x 250 mm
- Table broadening right	638 x 250 mm
- Table length extension back side	430 x 320 mm

### Logistic Data

- Product weight	21.32 kg
- Gross weight single packaging	28.25 kg
- Dimensions single packaging	735 x 615 x 365 mm
- Pieces per export carton	1 Pieces
- Gross weight export carton	28.25 kg
- Dimensions export carton	735 x 615 x 365 mm
- Container quantity (20"/40"/40"HC)	162   342   399

