Information requirements for electric local space heaters

| Item | Symbol | Value | Unit | Item | Unit |
|-------------------------------------|--------------------|-------|------|--|------|
| Heat output | | | | Type of heat input, for electric storage local space heaters only (select one) | |
| Nominal heat output | P _{nom} | 0,8 | kW | manual heat charge control, with integrated thermostat | - |
| Minimum heat output (indicative) | P _{min} | N.A. | kW | manual heat charge control with room and/or outdoor temperature feedback | - |
| Maximum contin- uous heat output | P _{max,c} | 0,8 | kW | electronic heat charge control with room and/or outdoor temperature feedback | - |
| Auxiliary electricity consumption | | | | fan assisted heat output | - |
| At nominal heat output | el_{max} | 0,000 | kW | Type of heat output/room temperature control (select one) | |
| At minimum heat output | el_{min} | 0,000 | kW | single stage heat output and no room temperature control | No |
| In standby mode | el _{SB} | 0,000 | kW | Two or more manual stages, no room temperature control | No |
| | | | | with mechanic thermostat room temperature control | Yes |
| | | | | with electronic room temperature control | No |
| | | | | electronic room temperature control plus day timer | No |
| | | | | electronic room temperature control plus week timer | No |
| | | | | Other control options (multiple selections possible) | |
| | | | | room temperature control, with presence detection | No |
| | | | | room temperature control, with open window detection | No |
| | | | | with distance control option | No |
| | | | | with adaptive start control | No |
| | | | | with working time limitation | No |
| | | | | with black bulb sensor | No |