

Electric Welding Transformer

RT-EW 230

The RT-EW 230 electric welding set can be powered with either 230 V or 400 V. An integrated appliance socket on the rear of the welding set allows external tools such as an angle grinder to be connected to it. Mobility for working is ensured by the ergonomic telescoping handle and the large wheels. The practical electrode holder and cable store keep the workplace tidy and thus enhance safety.














Features

- Female connection (230 V) with overload switch (6 A) at the rear side for external tools
- Continuously-adjustable welding current
- Turbo cooling by integrated cooling fan
- Convenient electrode storage
- Operating with 230/400 V
- Main cable 400 V
- Adapter cable to 230 V
- Thermo cut out with indicator light
- Ergonomically shaped transport handle
- Welding shield included








Welding shield included

RED RT-EW 230

Electric Welding Transformer





Female connection (230 V) with overload switch (6 A) at the rear side for external tools

Convenient electrode storage

Large wheels for easy transport

Sturdy metal housing

Rotary switch for nominal voltage 230V/400 V

Thermo cut out with indicator light

Continuously-adjustable welding current

Continuously adjustable

telescopic handle

Hook for cable reel

Stable supporting stand



Adapter cable to 230 V



Technical Data

Type: RT-EW 230

Logistic Information

Art.-No.: 15.440.71 **Ident-No.:** 01017

Bar code: 4006825 541496 **Packaging:** 470 x 275 x 410 mm

 Sales unit:
 1 pc

 20":
 568 pcs

 40":
 -- pcs

 40" HC:
 -- pcs

Gewicht: 26.4 kg (gross)

■ Mains: 230 V/400 V ~ 50 Hz

No load voltage: 48 V

Fuse: 16 AWelding current: 60 - 160 A at 230 V

60 - 200 A at 400 V

Turbo cooling by integrated cooling

Electrodes Ø: 2.0 – 4.0 mm

Power input: 8.8 kVA at 22 A

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery. Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved.

File: S:\shared-pool\Product-Documentation\T-Produktbeschreibung\30_n0t\Originale_Englisch_PA04\1544071_01017.doc

Erstelldatum/create date: 15.10.2007 12:14:00Aktualisiert/up dated: 29.11.2007