



Submersible Pump NSP 60 i

Art.-No.: **41.705.08**

Bar code: **4006825508949**

Sales unit: **4 pcs**

Powerful and robust submersible pump to empty garden ponds, flooded basements and construction sites. The installed float switch controls the ON/OFF function of the pump. It takes foreign particles up to Ø15 mm in size. High quality of the materials, i. e. stainless steel-driving gear and top quality axial face seal warrants an almost maintenance-free and a long service life of product performance. An exact fine-tuning between motor and turbine blade wheel achieves performance-efficiency and above-average performance data.

Features:

- Carrying handle (1)
- Float switch (2)
- 5-pcs connection kit (3)



Technical data:

- | | |
|---------------------------|--------------------|
| - Mains: | 230 V ~ 50 Hz |
| - Power: | 600 watts |
| - Delivery capacity max.: | 17,000 l/h |
| - Delivery height max.: | 7.5 m |
| - Immersion depth max.: | 5 m |
| - Water temperature max.: | up to 35 degrees |
| - Hose connection: | 1 ½" female thread |
| - Foreign particles size: | up to Ø 15 mm |
| - Mains cable: | 10 m H07RN-F |
| - ON function: | approx. 50 cm |
| - OFF function: | approx. 5 cm |
| - Weight: | 7.0 kg |
| - Packing dimensions: | 175 x 135 x 355 cm |

Performance data:

Delivery height:	Delivery capacity:
2 m	max. 15,600 l/h
4 m	max. 12,900 l/h
6 m	max. 9,000 l/h



As special accessory available:

PVC-drainage hose 10 m / 1"

Art.-No.: **41.737.11**

Bar code: **4006825414707**

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved

File: G:\Webshop\T-Produktbeschreibung\60\Originale_Englisch_PA04\4170508_01025.doc

Erstelldatum / create date: 15.11.2005 9:02

Aktualisiert / up dated: 29.11.2005