

Battery charger WLGN 15

Art.-No.: **10.750.20**

bar code: 4006825101478

Sales unit: 2 pcs

Multipurpose battery charger for 6-12-24 volt car batteries. The charging current and voltage can be set by positioning with the knob (1) the required setting. With the built-in ammeter (2) the charging current be seen. Strong pole clamps (3) warrant optimal contact with the battery poles. The handle enables (4) one to carry the charger safely.

Supplied with:

Double insulated construction, sheet steel housing, built-in ammeter (2), knob for quick and normal charging and setting of the required voltage (1), overload- and false poling- and short circuit protection, mains cable with Europe plug (non earthed), charging leads with sturdy pole clamps (3).

Technical data:

Mains voltage: 230 V ~ 50 Hz
Charging voltage: 6 V / 12 V / 24 V

Weight: 6,3 kg
Packing dimension: 330 x 255 x 170 mm

Charging current at normal charging:

6 V: 6,5 A eff. / 4,4 A arithm.

12 V: 8,0 A eff. / 5,4 A arithm.

24 V: 7,0 A eff. / 4,7 A arithm.

battery capacity min. 20 Ah

battery capacity min. 20 Ah

battery capacity min. 10 Ah

Charging current at quick charge:

6 V: 15 A eff. / 10,4 A arithm.

12 V: 15 A eff. / 10,4 A arithm.

24 V : 10 A eff. / 6,8 A arithm.

battery capacity min. 42 Ah

battery capacity min. 34 Ah

battery capacity min. 13 Ah

