

## Heating Generator HGG 171 Niro

Art.-No.: 23.304.35

Bar code: 4006825502183

Sales unit: 1 pc

Due to the high efficiency design and construction of the unit it could be kept small and handy with a high output. The normal connection is to a 5 resp. 11 kg propane/butane gas bottle. The integrated Piezo ignition as well as the thermal cut-out against over heating cut off the gas and warrant a safe operation.) A gas hose and the pressure reducer is supplied as standard equipment.

Unit is not to be used for professional service!

For professional service to be used only in connection with gas hose rupture device according DIN 30693 (special accessory)

### Features:

- ON/OFF-switch for fan (1)
- gas valve button
- heating reflector made of galvanized sheet steel (2)
- housing made of stainless steel (3)
- carrying handle (4)
- Piezo ignition
- Back-fire safety device
- Piezo electrical flame safety
- Sole
- Mai

### Technical data:

- Mains: 230 V ~ 50 Hz, 38 W
- Nominal heat load: 17 KW
- Nominal air volume: 500 m<sup>3</sup>/h
- Nominal gas consumption: 1430 g/h liquid gas P/B
- Operating pressure: 300 mbar
- Type of gas propane/butane: class I.3
- Weight: 5,9 kg
- Packing dimensions: 460 x 235 x 325 mm



As special accessory available:

Gas hose rupture device

Art.-No.: 33.912.30

Bar code: 4006825338348