

## Heating Generator HGG 110 Niro

Art.-No.: 23.301.36

Bar code: 4006825552263

Sales unit: 1 pc

Due to the high efficiency design and construction of the unit it could be kept small and handy with a high output. The normal connection is to a 5 resp. 11 kg propane/butane gas bottle. The integrated Piezo ignition as well as the thermal cut-out against over heating cut off the gas and warrant a safe operation. A gas hose and the pressure reducer are supplied as standard equipment.

Unit is **not** to be used for professional service!

For professional service to be used only in connection with gas hose rupture device (special accessory) according DIN 30693.

### Features:

- ON/OFF-switch for fan (1)
- Gas valve button
- Heating reflector made of galvanized sheet steel (2)
- Carrying handle (3)
- Housing made of stainless steel (4)
- Piezo ignition
- Back-fire safety device
- Piezo electrical flame safety
- Solenoid valve
- Mains cable

### Technical data:

- |                               |                        |
|-------------------------------|------------------------|
| - Mains:                      | 230 V ~ 50 Hz, 38 W    |
| - Nominal heat load:          | 11.2 kW                |
| - Nominal air volume:         | 500 m <sup>3</sup> /h  |
| - Nominal gas consumption:    | 815 g/h liquid gas P/B |
| - Operating pressure:         | 300 mbar               |
| - Type of gas propane/butane: | class I.3              |
| - Weight net:                 | 3.35 kg                |
| - Weight gross:               | 5.7 kg                 |
| - Packing dimensions:         | 400 x 230 x 310 mm     |



### As special accessory available:

Gas hose rupture device

Art.-No.: 33.912.30

Bar code: 4006825338348