

The high performance garden pump is particularly suitable for garden irrigation with collected rain water. Other features are the large flow rate and its long service life. The Pump is powered by an asynchronous motor with thermal protection.

Features

- Handle (1)
- Pressure connection (brass female thread) (2)
- Water inlet (3)
- Suction connection (brass female thread) (4)
- Pump housing made of plastic material (5)
- Water drain (6)
- ON/OFF switch

Technical Data

- | | |
|--------------------------------|------------------------------------|
| ■ Mains: | 230 V ~ 50 Hz |
| ■ Power: | 800 W |
| ■ Delivery capacity max.: | 3,000 l/h |
| ■ Delivery height: | 36 m |
| ■ Pressure max.: | 3.6 bar |
| ■ Pressure/suction connection: | approx. 33.3 mm (R1) female thread |
| ■ Water temperature max.: | 35°C |
| ■ Suction height max.: | 8 m |
| ■ Product weight: | 6.1 kg |

Logistic Data

- | | |
|-----------------------|--------------------|
| ■ Net weight: | 6.4 kg |
| ■ Gross weight: | 6.7 kg |
| ■ Packing dimensions: | 370 x 210 x 260 mm |
| ■ Bar code: | 4006825 596205 |
| ■ Sales Unit: | 1 pc |

