



Radial Pull Saw UFZS 1800

Art.-No.: **43.406.61**

Bar-Code: 4006825507034

Sales Unit: 1 pc

The radial pull saw UFZS 1800 is equipped with powerful motor for cutting and moulding of long and hard materials. The multipurpose stopper and the precise guidance avoid cants and allow an exact repeat accuracy.


Special features of the UFZS 1800 are: saw table made of anodised aluminium, precise setting of cutting height, twin sawdust extraction and a magnifying glass to support reading of the scales. The table saw can be converted into a mitre saw in a few seconds.

Features:

- Saw blade protection with extraction dust (1)
- Aluminium guide rail (2)
- Multifunctional angle – stop (3) with eccentric clamp (4)
- Saw table made of anodised aluminium (5)
- Combined saw blade pull appliance and saw blade vertical adjustment (6)
- Saw blade angle adjustment with scale (7)
- Push stick
- Magnifying glass on scale setting

Technical data:

- Mains: 230 V ~ 50 Hz
- Power: 1800 watts S6 40%
- Rev./min.: 4300min⁻¹
- String length saw blade: 220 mm
- No. of teeth: 48
- Cutting height max: 73 mm/90°, 50 mm/45°
- Height adjustment: continuously 0 – 73 mm
- Table size: 620 x 455 mm
- Table height: 320 mm
- Saw blade rotation: -2° to 47°
- Dust extraction adaptor: 35 mm
- Weight: approx. 37 kg
- Packing dimension: 830 x 630 x 350 mm



As special accessory available:

- Carbide tipped saw blade
Ø 250 x Ø 30 mm 24 teeth
- Carbide tipped saw blade
Ø 250 x Ø 30 mm 48 teeth
- Carbide tipped saw blade
Ø 250 x Ø 30 mm 60 teeth

- Art.-No.: **43.111.10**
Bar-Code: 4006825431223
- Art.-No.: **43.111.11**
Bar-Code: 4006825431230
- Art.-No.: **43.111.13**
Bar-Code: 4006825503166

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen // Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten // Illustration similar (in design), production-wise modifications reserved

File: S:\shared-pool\Product-Dokumentation\T-Produktbeschreibung\30_n0t\Originale_Englisch_PA04\4340661_01014.doc

Erstelldatum / create date: 31.05.2005 15:48:00

Aktualisiert / up dated: 15.01.2010