

With this mini circular saw laminate or parquet floors can be cut very easily. Subsequent plunge cuts are also possible. The cutting depth is adjustable, thus neither the saw blade or underlieing materials will be damaged. Softstart and overload protection serve there as security.

Features

- Continuously adjustable cutting depth (1)
- Electronic overload protection (2)
- HSS saw blade (3)
- Integrated dust extraction
- Soft starting electronic
- Spindle lock
- Housing surface „softpainted“

Standard accessories

- HSS saw blade with 30 teeth
- HSS saw blade with 44 teeth
- Dust extraction hose (4)
- Tool for saw blade change (5)
- Transport and storage case (6)

Technical Data

- | | |
|--------------------------|------------------------------|
| ■ Mains: | 230 V ~ 50 Hz |
| ■ Power: | 500 W |
| ■ Idle speed: | 7,000 min ⁻¹ |
| ■ Cutting depth: | max. 12 mm |
| ■ Saw blade center hole: | Ø 11 mm |
| ■ HSS saw blade: | Ø 50.8 x Ø 11 x 1.3 mm, 30 T |
| ■ HSS saw blade: | Ø 50.8 x Ø 11 x 1.3 mm, 44 T |
| ■ Net weight: | 3.1 kg |
| ■ Gross weight: | 3.4 kg |
| ■ Packing dimensions: | 345 x 105 x 310 mm |
| ■ Bar code: | 4006825 556452 |
| ■ Sales unit: | 5 pcs |



As special accessories available:

5 pcs HSS saw blade set, 44 T

For cutting of wood, laminate and plastics

Art.-No.: 45.021.21

Bar code: 4006825 534207

5 pcs HSS saw blade set, 60 T

For cutting of laminate and aluminium

Art.-No.: 45.021.22

Bar code: 4006825 534214

5 pcs diamond cutting disc set

For cutting of flagstones

Art.-No.: 45.021.23

Bar code: 4006825 534221

6 pcs saw blade set

2x HSS Ø 50.8 x Ø 11 mm, 60 T

2x HSS Ø 50.8 x Ø 11 mm, 44 T

2x diamond Ø 50.2 x Ø 11 mm

Art.-No.: 45.021.24

Bar code: 4006825 543643