

## Portable Split Air Conditioner MSK 3500 C+H

Art.-No.: 23.602.26

Bar code: 4006825547382

Sales unit: 1 pc

The portable and compact air conditioner consists of two units and provides a comfortable indoor climate. The external unit (liquefier unit) and the inside unit (vaporiser unit) are associated with a 3 meter long cooling line. The external unit is set up in the free or hung up at a outside wall. The mobile inside unit is set up in the area which should be air-conditioned. The unit is completely assembled and directly ready for use. With the soft keys or with the remote control all operating levels can be set on the inside unit and also the air conditioner can be switched on/off. The thermostat regulation provides a well-balanced indoor climate. This model is suitable for rooms of max. 100 m<sup>3</sup>.

### Features:

- Large display (1)
- Vertically mechanically adjustable air discharge opening lamellas (2)
- 4 pcs castors (3)
- Air-intake filter with activated carbon filter (4)
- Remote control (5)
- 3 meter long, pre-assembled cooling line with "Quick"-connector (6)
- Wall fastening for external unit
- 2 pcs flat spanner

### Functions:

- Unit On / Off
- LED-Display
- Target – temperature attitude: +18°C up to +32°C
- Sleep mode adjustment
- Fan speed: 3-settings
- Operating level section (MODE): automatic, cooling, fan, heating
- Power-on time: 1-24h, Continuous operation

### LED-Display for:

- Actual temperature
- Target temperature
- Sleep mode on
- Fan speed
- Automatic, cooling, fan, heating
- Timer on
- Condensation water tank full

### Technical data:

- Free of FCKW (R410A)
  - Cooling quantity: 740 g
  - Energy-Efficiency-Class\*: C
  - EER / COP\*: 2.81 / 2.61
  - Energy consumption at cooling\*: 623 kWh/year
  - Mains: 230 V ~ 50 Hz
  - Cooling capacity\*: 3,500 W
  - Heating capacity\*: 2,980 W
  - Air circulation max.: 680 m<sup>3</sup>/h
  - Exhausted room humidity max. (30°C/80% RH): approx. 43l/day
  - Noise level inside unit: ≤ 54dB (A)
  - Noise level external unit: ≤ 62dB (A)
  - Dimensions inside unit approx.: 365x608x746 mm
  - Dimensions external unit approx.: 500x310x520 mm
  - Weight inside unit (net) approx.: 32 kg
  - Weight external unit (net) approx.: 13 kg
  - Weight complete with package: 48 kg
  - Packaging approx.: 1,150x400x780 mm
- \*Characteristics of EN 14511

