

Deep well pump TBP 1300 Niro

Art.-No.: 41.709.40

Bar code: 4006825528527

Sales unit: 1 pc

The robust deep well pump is most suitable for delivery of clear water from reservoir, well and shafts. The deep well pump is also able to pump the water up from large depths and because of the multi-stage rotor-system the water can be transfer with much pressure.

The integrated motor-thermo protection protects the pump against overloading.

The pump is equipped with an external switching box and a 20 meter long connecting cable.

The vertical pressure line connection with an integrated return valve consists of brass and has a 1 1/2" inside thread.

Technical data:

- Mains: 230 V ~ 50 Hz
- Power: 1300 W
- Delivery quantity max.: 5000 l/h
- Delivery height max.: 65 m
- Immersion depth max.: 20 m
- Water temperature max.: 35 °C
- Hose connection: 1 1/2" inside thread
- contaminant: clear water
- Mains cable: 2 m
- Connecting cable: 20 m
- Pump-Ø: 102 mm
- Plastic pump wheels: 10 pcs
- Weight: 16 kg
- Packing dimensions: 910 x 225 x 215 mm

Features:

- Robust pressure connection with brass insert and an integrated return valve
- Pump housing consist of rust-free stainless steel (1)
- stainless steel dirt trap (2)
- External switching box (3)
- Overload switch (4)
- ON / OFF switch (5)
- operation display (6)
- mains display (7)
- Drain cord (8)

Performance data:

