

Submersible Pump SP 350

Art.-No.: **41.705.79**

Bar code: **2052516400001**

Sales unit: **4 pcs**

Powerful and robust submersible pump to empty garden ponds, flooded basements and construction sites. It takes foreign particles up to Ø 30 mm in size. The pump is equipped with a float switch for automatic ON/OFF operation for a varying water level. The complete housing is made of an impact resistant material (plastic).

Features:

- Carrying handle (1)
- Universal connection for 1" and 1 ¼"-hose connection as well as 1"-male thread (2)
- 90° angel bracket with 1 ½" x 1 ½" male thread (3)
- Float switch (4)

Technical data:

- | | |
|---------------------------|--------------------|
| - Mains: | 230 V ~ 50 Hz |
| - Power: | 350 W |
| - Delivery capacity max.: | 7,000 l/h |
| - Delivery height max.: | 5 m |
| - Immersion depth max.: | 5 m |
| - Water temperature max.: | 35°C |
| - Hose connection: | 1 ½" female thread |
| - Foreign particles size: | Ø 30 mm |
| - Mains cable: | 10 m H05RN-F |
| - „ON“ function: | approx. 50 cm |
| - „OFF“ function: | approx. 5 cm |
| - Minimum immersion: | approx. 40 mm |
| - Weight: | 4.9 kg |
| - Packing dimensions: | 240 x 175 x 335 mm |



Performance data:

Delivery height:	Delivery capacity:
2 m	max. 4,500 l/h
3 m	max. 3,000 l/h
4 m	max. 1,300 l/h

As special accessory available:

Drainage hose 10 m / 1"
(material: PVC); Einhell

Art.-No.: **41.737.11**
Bar code: **4006825414707**

