



Submersible Pump KW 255/1

Art.-No.: **41.702.87**

bar code: **7611330163575**

sales unit: **4 pcs**

Ideal to empty flooded basements, tanks and containers, etc. The installed float switch controls the ON/OFF functions of the pump.

High quality of the material i.e. stainless steel- driving gear, top quality axial face seal, screwed cable locks made of stainless steel warrant an almost corrosion-free and a long service life. The complete housing is made of an impact resistant material (plastic).

Technical data:

| | |
|--------------------------------|--------------------|
| - Mains: | 230 V ~ 50 Hz |
| - Power: | 250 watts |
| - Delivery capacity max.: | 6200 l/h |
| - Delivery height max.: | 5.5 m |
| - Immersion depth max.: | 5 m |
| - Water temperature: | up to 35°C |
| - Foreign particles size max.: | Ø 3 mm |
| - Mains cable: | 10 m H05RN-F |
| - ON function: | ca. 50 cm |
| - OFF function: | ca. 5 cm |
| - Hose connection: | 1 ¼" female thread |
| - Minimum immersion: | 8 mm |
| - Weight: | 4.3 kg |
| - Packing Dimensions: | 240 x 175 x 310 mm |

Features:

- Carrying handle (1)
- Float switch (2)
- 90 ° angle bracket with 1 ¼" x 1 ¼" male thread (3)
- Universal connection for 1" and 1 ¼" hose connection as well as 1" male thread (4)

Performance data:

| | |
|------------------|--------------------|
| Delivery height: | Delivery capacity: |
| 1 m | max.: 4800 l/h |
| 2 m | max.: 3600 l/h |
| 3 m | max.: 2400 l/h |
| 4 m | max.: 1500 l/h |



As special accessory available:

Drainage hose 10 m / 1" (material: PVC)

Art.-No.: **41.737.11**
bar code: **4006825414707**

