

The deep well pump with automatic function switches the device on automatically when water is required and also switches it off again. The clean water can be pumped to a max. height of 55 m thanks to the 8-stage impeller system. An immersion depth of max. 19 m and the slimline design make the pump suitable for use in deeper lying and constricted water reservoirs as well. The powerful 1,100 W motor pumps 6,000 l/h. A long service life is guaranteed by the stainless steel housing and high-quality mechanical seal. The integrated dry-run safeguard protects the pump against damage if the water supply is interrupted. The pump is equipped with an easily accessible hose connection on the top with an integrated nonreturn valve.

Features & Benefits

- Automatic function
- Dry running protection
- Robust pressure connector with stainless steel insert
- Pump housing made of rust-proof high-grade steel
- 8-stage pump wheels for high delivery pressure
- With integrated non-return valve
- High-quality mechanical seal for a long service life
- Stainless steel dirt sieve
- Easily reachable hose connection on the pump's topside
- 2 suspension eyelets
- 22 m rope

Technical Data

- Mains supply	220-240 V 50 Hz
- Power	1100 W
- Max. delivery capacity	6000 L/h
- Max. delivery height	55 m
- Max. immersion depth	19 m
- Max. water temperature	35 °C
- Hose connection	33,3mm (G1 IG)
- Power cord	22 m H07RN-F
- Pump diameter	98 mm



Logistic Data

- Product weight	10.15 kg
- Gross weight single packaging	15.4 kg
- Dimensions single packaging	955 x 211 x 221 mm
- Pieces per export carton	1 Pieces
- Gross weight export carton	15.4 kg
- Dimensions export carton	955 x 211 x 221 mm
- Container quantity (20"/40"/40"HC)	630 1260 1550