



Mobile and compact air conditioner, which provides a comfortable indoor climate. Cooling and dehumidifying in one unit. The unit is completely assembled and ready for service after the exhaust hose has been connected.

With soft keys all operating levels can be set and also the air conditioner can be switched on/off. The thermostat regulation provides a well-balanced indoor climate. This model is suitable for rooms of max. 95m³.



MA 110 Portable Air Conditioner

Logistic information:

Type:	MA 110	Sales unit	1 pc
Art.-No.:	23.602.20	20``:	92 pcs
Ident-No.:	01037	40``:	196 pcs
Bar code	4006825 534672	40`` HC:	292 pcs
Packaging:	695 x 395 x 887 mm	Weight:	38.0 kg (brutto)



Large, foldable display with backlight

Carrying handle



Mains cable storage space with coverage



4 pcs castors

Air discharge opening lamellas are adjustable mechanically in horizontal position



Remote control

Functions:

- LCD-Display, with backlight
- Target – temperature attitude: +18°C up to +30°C
- Fan speed: 3-settings
- Operating level section (MODE): Cooling, Dehumidifying, Ventilation
- „Swing“ - Function
- Temperature display reversible °C / °F
- Input delay: 0.5 to 24 h
- Power-on time: 0.5 – 24h, Continuous operation
- Unit On/Off

LCD-Display for:

- Actual temperature
- Target temperature
- Timer on
- Fan speed
- Cooling, Dehumidifying, Ventilation
- Swing - Function on
- Condensation water tank full

Features:

- large, foldable control panel
- Air suction filter
- Air discharge opening lamellas are adjustable mechanical in horizontal position
- Condensate returns during the cooling operation – no condensate box deflation necessary
- Integrated condensation box (approx. 1.2 litre volume)
- Air dehumidifier – function (constant dehydration over condensation hose)
- Mains cable storage space with coverage
- exit air hose with adapter
- 4 pcs castors
- remote control

Technical data:

- Free of FCKW (R407C)
- Energy-Efficiency-Class: A
- EER / COP: 2.51 / -
- Energy consumption at cooling: 650 kWh / year
- Mains: 230 V ~ 50 Hz
- Cooling capacity: 3.266 W
- Air circulation max.: 430 m³/h
- Exhausted room humidity max. (30°C/80% RH): approx. 70 l/day
- Quantity of coolant: 580 g
- Noise level: ≤55dB (A)
- Weight (net): 34 kg
- Characteristics of: EN 14511

Logistic information:

Type:	MA 110	Tool:	Portable Air Conditioner
Art.-No.:	23.602.20	VE:	1 pc
Ident-No.:	01037	20`:`	92 pcs
Bar code	4006825 534672	40`:`	196 pcs
Packaging:	695 x 395 x 887 mm	40``HC:	292 pcs
		Weight:	38.0 kg (brutto)

