

# Submersible pump GLSP 1007

**Art.-No.: 41.707.50**

**Bar code: 23224537**

**Sales unit: 1 pc**

The powerful and robust submersible pump for draining garden ponds, flooded basements and construction sites. Capable of handling foreign particles up to Ø 20 mm in size. High quality with materials as example rust-free stainless steel – motor shaft and high-quality control leakage shaft seal provides as far as possible maintenance-free and long-lived use. The optimal tuning between engine and paddle-wheel lead to an enormous effectiveness of the performance data.

## Technical data

- Mains: 230 V ~ 50 Hz
- Power: 1,000 W
- Delivery quantity max.: 20,000 l/h
- Delivery height max.: 8 m
- Immersion depth max.: 5 m
- Water temperature: max. 35 °C
- Foreign particles size: Ø 20 mm
- Main cable length: 10m H07RN-F
- Switch point ON: approx. 50 cm
- Switch point OFF: approx. 5 cm
- Hose connection: ca. 47,8 mm (1 ½" female thread)
- Type of protection: IPX 8
- Product weight: 6.9 kg

## Logistic data

- Net weight: 7.1 kg
- Gross weight: 7.6 kg
- Packing dimensions: 235 x 170 x 355 mm

## Performance data:

Delivery height	Delivery capacity
2 m	18,200 l/h
4 m	14,800 l/h
6 m	10,400 l/h

## Scope of delivery: 5-parts connection kit



## Features

- Handle (1)
- Float switch (2)
- 1 x connection angle for hose connectors (3)
- 1 x 90 ° angel bracket 38 mm (1 ½") male thread (4)
- Universal connection for 19 mm (¾"), 25 mm (1"), 32 mm (1 ¼") and 38 mm (1 ½") hoses

