



Einhell

CLASSIC

Hand Lever Winch

TC-LW 2000

Item No.: 2260150

Ident No.: 11018

Bar Code: 4006825643244

The Einhell TC-LW 2000 hand lever winch is suitable for pulling and tensioning loads with a maximum tensile load of 2,000 kg and a maximum useable distance of 1.6 meters. The product is supplied with a 3.3 meter twist-free wire cable (Ø 6 mm) and a guide roller with load hook which has a retention latch. The retention latch prevents the load from being unhooked accidentally. An automatic brake secures the load in every position. There is a safety clip to prevent a complete unrolling of the cable. The winch comes with a tensioning spring for releasing the retaining catch easily. The hand lever winch is not suitable for lifting and lowering loads.

Features & Benefits

- 3.3 m twist-free wire cable (Ø 6 mm)
- Incl. guide roller with load hook & retention latch
- Retention latch prevents the load being unhooked accidentally
- An automatic brake secures the load in every position
- Tensioning spring for releasing the retaining catch easily
- Suitable for pulling and tensioning loads
- Not suitable for lifting and lowering loads
- The max. payload with guide roller is 2000kg
- Safety clip prevents complete unrolling of the cable




Technical Data

- | | |
|----------------------------------|---------|
| - Max. useable distance | 1.6 m |
| - Steel cable diameter | 6 mm |
| - Steel cable length | 3.3 m |
| - Automatic brake | yes |
| - Max. payload with guide roller | 2000 kg |

Logistic Data

- | | |
|--------------------------------------|--------------------|
| - Product weight (kg) | 5.21 |
| - Gross weight (kg) | 5.53 |
| - Dimensions single packaging | 141 x 98 x 675 mm |
| - Pieces per export carton | 4 Pieces |
| - Gross weight of export carton | 22 kg |
| - Dimensions export carton | 705 x 215 x 290 mm |
| - Container quantity (20"/40"/40"HC) | 1920 3840 |



SAFETY HOOK



AUTOMATIC STOP



GUIDEROLLER




TENSIONING SPRING



SOFTGRIP




max. 2000 kg



USABLE
DISTANCE

max. 1.6 m



CABLE

6 mm