

Split-Air Conditioner SKA 3500 C + H

Art.-No.: 23.653.22

Bar-Code: 4006825234732

Sales unit: 1 pc

Air conditioner for **cooling and heating** for wall installation.

Automatic de-humidifying of air in a room

Complete with remote controlled transmitter and 4 m connecting copper tubes with flexible insulation (max. 15 m possibly).

Time programming device for ON/OFF.

Easy installation of the air conditioner with a **cooling capacity of 3.500 watts** and a heating capacity of **3.800 watts**. Ideal for large rooms until approx. 117 m³. The unit consists of 2 parts, an outdoor part and one for indoors, in order to allow quick cooling and warrant an optimal noise level.

3 setting of fan speed with a maximum speed of 520 m³/h.

With the **automatic de-humidification** the units evaporates from its surrounding approx **1.3 l/h** excess humidity.

Timer for programme settings, Automatic- and night functions.

All functions can be set with the **remote controlled transmitter**. Supplied with LCD indicator. Motorized ventilation lamella in the indoor unit.

Dimensions:

Indoor unit (WxDxH): 790 x 275 x 180 mm

Outdoor unit (WxDxH): 830 x 545 x 255 mm

Weight:

Indoor unit: 10 kg

Outdoor unit: 36 kg

Weight total gross: 54 kg

Packing dimensions 1030 x 520 x 960 mm

(WxDxH):

Features:

- Air suction grid (1)
- LCD-display (2)
- Air escape plate fin (3)
- Remote control (4)
- Pipe connection (5)
- Fan (6)

Technical data:

- Free of FCKW (R407C)
- Energy-Efficiency-Class: B
- EER / COP: 3,02 / 3,42
- Energy consumption when cooling: 580 kWh per year
- Cooling capacity: 3.500 watts
- Heating capacity: 3.800 watts
- Air throughput: 520 m³/h
- Capacity of humidity reduction: 1,3 l/h
- Mains: 230 V ~ 50 Hz
- Refrigerant quantity: approx. 900g for 4 m of tube (for each further meter 20g encloses)
- Noise level: Indoors: 40 dB (A)
Outdoors: 55 dB (A)

Characteristics according to EN 14511



Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved
File: S:\shared-pool\Product-Dokumentation\T-Produktbeschreibung\30_n0\Originale_Englisch_PA04\2365322_01012.doc

Erstelldatum / create date: 12/08/2004 16:17:00

Aktualisiert / up dated: 14/07/2006