

**RED**

RT-TS 1825 U

Table Saw with Underframe

The RT-TS 1825 U table saw has been designed for stationary and mobile application. The easy-to-install table extensions provide a large work surface where the parallel stop can be used across the entire width. The RT-TS 1825 U has been designed for multi-purpose applications: ripping and crosscuts of lumber, chipboard, plywood, multiplex board, veneered board and plastics. Thanks to its V-belt drive the table saw is very quiet and smooth running. Its compact design, ease of handling during transport and its powerful performance make ideal for outdoor use, e.g. at construction sites and for interior decorating work. The saw can be tilted up to 45° for mitre cuts. The sturdy underframe turns the table saw into a sturdy stand-alone saw which can be used at optimum working heights.



Features

- Toolless disassembly of extension table
- Parallel stop with non-stop aluminium guide on total broadness usable
- Anodised table surface for advanced anti-friction property
- Saw blade angle adjustment with scale
- Saw blade height adjustment
- Cross fence with angle scale
- Saw blade protection with dust exhaust device
- Lens for number scale
- Push stick with clamp



RED

RT-TS 1825 U

Table Saw with Underframe

Anodised table surface for advanced anti-friction properties

Table broadening and table extension toolless removable

Powder-coated housing

Handles for easy transport

Easy mountable underframe

Saw blade protection with dust exhaust device

Parallel stop with aluminium guide

Crimping flange to fix the parallel stop

Cross fence with angle adjustment

Sägeblattwinkelverstellung mit Skala

Saw blade height adjustment



As special accessories available:

TCT saw blade Ø 250 x Ø 30 mm 36 teeth
 TCT saw blade Ø 250 x Ø 30 mm 60 teeth
 TCT saw blade PRO Ø 250 mm 80 teeth AK
 TCT saw blade PRO Ø 250 mm 80 teeth

Art.No.:

45.020.37
 43.111.13
 45.021.52
 45.021.53

Logistic Information

Type:	RT-TS 1825 U
Art.-No.:	43.406.48
Ident-No.:	01017
Bar code:	4006825 541410
Packing:	750 x 575 x 400 mm
Sales unit:	1 pc
20'':	150 pcs
40'':	300 pcs
40'' HC:	-- pcs
Net weight:	33.7 kg
Gross weight:	37.0 kg

Technical Data

■ Mains:	230 – 240 V ~ 50 Hz
■ Power:	1,800 W (S6 40%)
■ Idle speed:	5,700 min ⁻¹
■ Cutting height max.:	73 mm (90°), 53 mm (45°)
■ Carbide-tipped saw blade:	Ø 250 x Ø 30 x 2.4 mm (24 T)
■ Rotation range:	0° – 45°
■ Cross fence tiltable:	2 x 0° – 45°
■ Table size:	625 x 440 mm
■ Table broadening left/right:	625 x 250 mm
■ Table length extension back side:	400 x 440 mm
■ Connection for dust exhaust:	Ø 36 mm