



# Einhell

## **EXPERT** TE-AC 480/100/10 D Air Compressor

**Art.-No. 40.102.31**

The 2 cylinders, the powerful 400 volt engine and the belt drive cares for a high intake capacity. The 10 bar of the large 100 litre vessel allows a variety application spectrum and by using of highgrade components a very long runtime is secured. By quick couplings the vessel pressure or a lower regulated working pressure can be taken out. For the regulated working pressure 2 quick couplings are available. Regulated compressed air is cleaned by a filter pressure reducer with metal housing from condensation, what for example with paint work is necessary. Due to large wheels and guide rollers the compressor is mobile.

### Features



- Filter pressure reducer with metal housing and condensate separator
- High running time
- 2 cylinder air compressor
- Belt drive
- 100 litre tank
- Pressure switch
- Pressure gauge and quick-release coupling for unregulated tank pressure
- 1 pressure gauge and 2 quick-release couplings for regulated working pressure
- Non-return valve
- Safety valve
- 2 guide rollers and 2 large wheels
- 10 years warranty against rusting through of the tank

### Technical Data

- Mains: 400 V 3~ 50 Hz 3-phase
- Power: 3.0 kW (4 HP)
- Idle speed: 1,310 rpm
- Intake capacity: 480 l / min
- Output power: at 0 bar: 389 l/min  
at 4 bar: 348 l/min  
at 7 bar: 308 l/min
- Tank capacity (liters): 100 l
- Operating pressure: max. 10 bar
- No. of cylinders: 2
- Product weight: 81.0 kg

### Logistic Data

- Net weight: 81.0 kg
- Gross weight: 92.0 kg
- Packing dimensions: 1,010 x 410 x 895 mm
- Bar Code: 4006825 593143
- Sales Unit: 1 pc



Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery. Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved.

File: \\aa-fas-2\office\shared-pool\Product-Dokumentation\T-Produktbeschreibung\30\_n0t\Originale\_Englisch\_PA04\4010231\_11012.doc

Erstelldatum/create date: 07.03.2013 09:00:00Aktualisiert/up dated: 05.03.2014