



# Einhell

**GREY**

## Double steps inside pressure controller 50 mbar

**Art.-No. 23.323.99**

This household control is legally required in Germany if you want to run a gas appliance (e.g. gas stove, gas cooker or gas oven) in a closed room (e.g. in a kitchen).

The controller is correspond to the standards EN 12864 and DIN 4815 F1-t and is suitable for households (all inside constructions) according to TRF 1996-5.2.7.2 and for all commercial used LPG installations (inside and outside) according to UVV BGV D34 §11 para. 3 and 4.

### Features

- Pressure gauge for checking the tightness of the system
- Thermal shut-off device for automatically shutting off gas flow when temperature is over 100 °C
- Regulator with overpressure safety device. (If one of the both control steps breakdown, e.g. by dirt or other foreign material on the valve, the other control step take over a pressure reduction to max. 100 mbar. If one of the both control steps is failed, the controller must be replaced.

### Technical data

- Inlet pressure: 0.3 – 16 bar
- Outlet pressure: 50 mbar
- Inlet connection: KLF (W21,8 x 1/14") left-hand thread
- Outlet connection: G1/4 LH-KN DIN 8542
- Suitable for all standard 5 and 11 kg propan gas bottles
- Product weight: 0.36 kg

### Logistic data

- Net weight: 0.36 kg
- Gross weight: 0.38 kg
- Packing dimensions: 119 x 90 x 87 mm
- Bar code: 4006825585735
- Sales unit: 1 pc

