



Power Generator (Petrol/Gas)

TE-IG 1900 DF

Item No.: 4152630

Ident No.: 21012

Bar Code: 4006825669619

The Einhell generator (petrol/gas) TE-IG 1900 DF supplies power anywhere, thanks to its low-emission 4-stroke drive motor. The generator can run on both gas (propane, LPG) and petrol. It provides up to 1800 watts of continuous power and 1900 watts of peak power in petrol mode, and 1600 watts of continuous power and a peak of 1700 watts when operated with gas. The inverter technology delivers power without voltage spikes. The power generator has 2x 230 V sockets, 2x USB ports and one 12 V connection. An overload switch and low-oil cut-out are provided for safety. The trolley-like design makes for easy transport.

Features & Benefits

- Option to operate with petrol or gas (propane, LPG)
- Inverter technology for power without voltage spikes
- Powerful, robust and low-emission 4-stroke engine
- Gauge for level in fuel tank
- 2x 230 V/50 Hz sockets
- 2x USB ports (1x 1.0 A and 1x 2.1 A)
- 1x 12 V connection for charging e.g. vehicle batteries
- Closed design for quiet operation.
- Trolley system and carrying handle for portable applications
- Voltmeter to display voltage
- Overload switch and low-oil cut-out for long-lasting operation

Technical Data

- Type of generator Synchronous - with Inverter - Max. watts 1900 W 1700 W - Max. watts - Gas 1800 W - Running Watts (max) - Running Watts (max) - Gas 1600 W - Continuous power at 12 V DC 100 W - Frequency 50 Hz 2 Pieces - 230 V socket

- 12 V DC connection 1 Pieces - Engine type four-stroke, air cooled

- Engine displacement 79.8 cm³ 5300 min^-1 - Engine speed

- Fuel Petrol (unleaded) / E10 and

Gas (LPG)

- Capacity of fuel tank 4.2 L - Running time with 2/3 load (Petrol) 5.9 h - Running time with 2/3 load (11 kg 6.9 h Propane)

- Sound power level Lwa 95 dB (A)





















Logistic Data

- Product weight (kg) 23.7 - Gross weight (kg) 27.1

- Dimensions single packaging 575 x 380 x 597 mm

- Pieces per export carton 1 Pieces 27.1 kg - Gross weight of export carton

- Dimensions export carton 580 x 380 x 600 mm - Container quantity (20"/40"/40"HC) 174 | 360 | 480