

## Heating Generator HGG 171 Niro

Art.-No.: 23.304.35

Bar code: 4006825502183

Sales unit: 1 pc

Due to the high efficiency design and construction of the unit it could be kept small and handy with a high output. The normal connection is to a 5 resp. 11 kg propane/butane gas bottle. The integrated Piezo ignition as well as the thermal cut-out against over heating cut off the gas and warrant a safe operation. A gas hose and the pressure reducer are supplied as standard equipment.

Unit is **not** to be used for professional service!

For professional service to be used only in connection with gas hose rupture device (special accessory) according DIN 30693.

### Features:

- ON/OFF-switch for fan (1)
- Gas valve button
- Heating reflector made of galvanized sheet steel (2)
- Carrying handle (3)
- Housing made of stainless steel (4)
- Piezo ignition
- Back-fire safety device
- Piezo electrical flame safety
- Solenoid valve
- Mains cable

### Technical data:

- Mains: 230 V ~ 50 Hz, 38 W
- Nominal heat load: 17 kW
- Nominal air volume: 500 m<sup>3</sup>/h
- Nominal gas consumption: 1430 g/h liquid gas P/B
- Operating pressure: 300 mbar
- Type of gas propane/butane: class I.3
- Weight: 5.9 kg
- Packing dimensions: 460 x 235 x 325 mm



### As special accessory available:

Gas hose rupture device

Art.-No.: 33.912.30

Bar code: 4006825338348