



**RED**

# RT-TC 560 U

## Tile Cutting Machine

The tile cutting machine can be mounted quickly on the serial type support stand and is therefore suitable for mobile as well as stationary service.

With the unit one can cut wall- and floor tile, split tiles etc. Angle and double mitre cuts are possible and also jolly cuts.

The turbo-diamond cutting disc is cooled with the integrated pump for cooling liquids and thus an almost dust free operation is possible.

A laser projects the cutting line onto the work piece.



### Features

- Aluminium work table
- RCD-Plug for unit safety
- Motor guidance continuously tiltable from 0°- 45°
- Motor guidance 4-fold ball bearings
- Sturdy feet
- Aluminium guide rail
- Angle stop with scale for exact cuts
- Large water pan
- Turbo-diamond cutting disc
- Sturdy machine housing made of sheet steel
- Integrated water pump
- Including laser





**RED**

# RT-TC 560 U Tile Cutting Machine



Continuously tiltable motor guidance settings 0°- 45°



Angle stop with scale for exact cuts



Large water pan with integrated water pump



RCD-plug for unit safety



As special accessory available:  
Turbo diamond cutting disc Ø 200 x Ø 25.4 mm

Art.No.:  
43.011.75

## Logistic Information

<b>Type:</b>	<b>RT-TC 560 U</b>
<b>Art.-No.:</b>	43.012.80
<b>Ident-No.:</b>	01017
<b>Bar code:</b>	4006825 542134
<b>Packing:</b>	890 x 490 x 365 mm
<b>Sales unit:</b>	1 pc
<b>20'':</b>	168 pcs
<b>40'':</b>	366 pcs
<b>40'' HC:</b>	427 pcs
<b>Net weight:</b>	26.2 kg
<b>Gross weight:</b>	30.6 kg

## Technical Data

■ Mains:	230 V ~ 50 Hz
■ Power:	800 W
■ Idle speed:	2,950 min <sup>-1</sup>
■ Working table:	594 x 385 mm
■ Cutting depth max.:	90°: 30 mm / 45°: 25 mm
■ Cutting length max.:	520 mm
■ Mitre cuts:	0° - 45°
■ Diamond disc:	Ø 200 x Ø 25.4 mm
■ Insulation class:	IP 54