

RT-CC 315 UD

Table Cross Cut Saw



The RT-CC 315 UD is a powerful cross cut saw, easy to handle and suitable for a wide range of applications.

Ideal for ripping solid woods and precise cross-cutting of work pieces. Equipped with a precise operating slide, parallel guide rail with eccentric locking lever, angle settings and twin dust extraction adaptor.

Precise setting of the cutting height as well as the lens (easy reading on the scale) allow a more easier and exact working with the cross cut saw.

For mobile application, the RT-CC 315 UD has been equipped with an undercarriage and handles for transport by a single person.









Features

- Saw and push table made of anodised aluminium
- Aluminium guide rails for precision cutting
- Rotation range saw blade 0 45° with angle scale
- Continuous saw blade height adjustment 0-73 mm
- Including wheels, handles and undercarriage
- Cross fence with angle scale
- Guide rail for parallel cuttings
- Parallel guide with eccentric clamp
- Lens for number scale
- Integrated dust extraction device



RT-CC 315 UD

Table Cross Cut Saw



Saw and push table made of anodised aluminium

Saw blade protection with suction hose



Cross fence with angle scale

parallel cuttings

Foldable end stop

Parallel guide with eccentric clamp

Saw blade angle adjustment

Saw blade height adjustment



Integrated dust extraction



As special accessories available:

TCT saw blade Ø 315 x Ø 30 mm, 24 teeth TCT saw blade Ø 315 x Ø 30 mm, 48 teeth

Art.No.: 45.020.60 45.020.11

Logistic Information

Technical Data

Included wheels and handles for easy transport by one person

Type:	RT-CC 315 UD
ArtNo.:	43.406.81
Ident-No.:	01017
Bar code:	4006825 541021
Packaging:	1,130 x 710 x 440 mm

 Sales unit:
 1 pc

 20":
 75 pcs

 40":
 150 pcs

 40" HC:
 -- pcs

 Net weight:
 68.0 kg

 Gross weight:
 70.0 kg

Mains: 400 V 3 ~ 50 Hz
 Power: 2,200 W S6 40%
 Idle speed: 2,750 min⁻¹

Number of teeth: 24

Saw blade: Ø 315 x Ø 30 x 3.6 mm
 Cutting height max.: 73 mm/90°, 49 mm/45°

Height adjustment continuous: 0 – 73 mm
 Table size: 800 x 350 mm
 Size of slide table: 1,000 x 300 mm

Slide length: 600 mm
 Saw blade rotation: 0 – 45°

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery. Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved.

File: S:\shared-pool\Product-Documentation\T-Produktbeschreibung\30_n0t\Originale_Englisch_PA04\4340681_01017.doc

Erstelldatum/create date: 16.06.2008 16:48:00Aktualisiert/up dated: 14.01.2010