

Submersible Pump TP 260/1

Art.-No.: **41.702.85**

bar code: 4006825416282

sales unit: 4 pcs

The 4 kg lightly submersible pump is ideal to empty flooded basements, tanks and containers, etc. The installed float switch controls the ON/OFF functions of the pump. With a delivery capacity of max. 6300 l/h and a delivery height of max. 5,5 m handling of any delivery problems could be easily solved.

High quality of the material and design i.e. stainless steel- driving gear, warrant an almost corrosion-free and a long service life.

Technical data:

- Mains: 230 V ~ 50 Hz
- Power: 250 watts
- Delivery capacity max.: 6300 l/h
- Delivery height max.: 5,5 m
- Immersion depth max.: 5 m
- Water temperature: up to 35°C
- Foreign particles size: max. Ø 3 mm
- Mains cable: 10 m H05RN-F
- ON function: ca. 50 cm
- OFF function: ca. 5 cm
- Hose connection: 1 ¼" female thread
- Minimum immersion: 8 mm
- Weight: 4,2 kg
- Packing Dimensions: 24,5 x 17,5 x 31 cm

Features:

- Carrying handle (1)
- Float switch (2)
- Universal connection (3)

Performance data:

Delivery height:	Delivery capacity:
1 m	max.: 4800 l/h
2 m	max.: 3600 l/h
3 m	max.: 2400 l/h
4 m	max.: 1500 l/h

