



Sliding Cross cut- and mitre table saw With underframe KGZ 3300 UG – R

Art.-No.: **43.006.52**

bar code: 4006825507041

sales unit: 1 pcs


The sliding cross cut- and mitre table saw warrants a clean and smooth cut of wooden parts without problems. Double mitre cuts are possible with its tilting and swivelling motor-head. Due to its sliding feature the saw can cut 330 mm wide and therefore wide panels and laminate floorboard can be cut in one go. The undercarriage with adjustable fixing rolls makes the machine ideal for stationary or permanent service.

Features:

- Carbide tipped saw blade (1)
- Rotating table for precise angle cuts ranging -45° to $+45^{\circ}$ (2)
- Motor head continuously tiltable from 0° to $+45^{\circ}$
- Including two work piece support clamp (3)
- Clamping device for fixation of the work piece (4)
- Key for saw blade change (5)
- Including dust bag and transport locking system
- Including undercarriage with fixing rolls

Technical data:

- Mains: 230 V ~ 50 Hz
- Power: 1600 watts
- Idle speed n_0 : 4.200 min^{-1}
- Saw blade: $\text{Ø } 305 \times \text{Ø } 30 \times 3,2 \text{ mm}$
- No. of teeth: 60
- Turning range: $-45^{\circ} \text{ } 0 \text{ } +45^{\circ}$
- Panels max.: 330 mm
- Mitre cut: 0° to 45° to the left
- Cutting width at max 45° : $215 \times 102 \text{ mm}$
- Cutting width at max 90° : $330 \times 102 \text{ mm}$
- Cutting width at max. $2 \times 45^{\circ}$: $215 \times 65 \text{ mm}$
(Double mitre cut)
- Length of the fixing at the underframe: max. 190 cm
- Weight: 59,5 kg
- Packing dimension: $1065 \times 725 \times 490 \text{ mm}$



As special accessory available

Carbide – tipped blade
 $\text{Ø } 305 \times \text{Ø } 30 \times 3,2 \text{ mm}$ 60 teeth

Art.-No.: **45.020.59**
Bar-Code: **4006825505450**