



# NPHW 5500

## Home Water Works

Art.-No. 41.734.23

The water works unit pumps water from wells and cisterns automatically with stable water pressure. The water works is especially powerful due to five serial placed blade wheels. Toilets, washing machines and garden watering are just a few of its numerous applications. The housing of the pump and the vessel are made of corrosion resistant stainless steel, therefore not rusty colouring of the water supplied. The unit is powered by a sturdy asynchronous motor with thermal protection. The water works is supplied complete with pressure switch and pressure gauge.

### Features

- Pressure switch (1)
- Stainless steel pump housing (6)
- Water drain plug (4)
- Stainless steel tank 24 ltr. (3)
- Water filler screw (2)
- Pressure gauge
- 5 pcs plastic blade wheels
- Pre-filter (5)
- 1 connection nipple approx. 33,3 mm (R1) male thread
- 1 connection adapter approx. 33,3 mm (R1) male thread and approx. 42 mm (R1¼) female thread

### Technical Data

- Mains: 230 V ~ 50 Hz
- Power: 1,150 W
- Delivery capacity max.: 5,500 l/h
- Delivery height max.: 48 m
- Delivery pressure max.: 4.8 bar
- Activation pressure max.: 1.5 bar
- Cut-off pressure max.: 3 bar
- Suction height max.: 8 m
- Tank volume: 24 litre
- Suction connection: approx. 33.3 mm (R1) female thread
- Pressure connection: approx. 42 mm (R1¼) male thread
- Water temperature: up to 35 °C
- Extra long power cord: 5 m
- Product weight: 17.3 kg



### Logistic Data

- Net weight: 17.3 kg
- Gross weight: 20.3 kg
- Packing dimensions: 580 x 340 x 700 mm
- Bar code: 4006825 589689
- Sales unit: 1 pc

