



NPGP 5500 Garden Pump

Art.-No. 41.822.42

The high performance garden pump is particularly suitable for the garden irrigation with collected rain water. The garden pump is especially powerful due to five serial placed plastic blade wheels. Other features are the large suction capacity and its long service life. The Pump is powered by an asynchronous motor with thermal protection. The pump housing is made of corrosion resistant stainless steel, therefore durable and not rusty colouring of the water supplied.

Features

- Handle (1)
- Stainless steel pump housing (2)
- Water drain plug (3)
- Pre-filter (4)
- Water filler screw (5)
- ON/OFF switch
- 5 plastic blade wheels
- 1 connection nipple approx. 33,3 mm (R1) male thread
- 1 connection adapter approx. 33,3 mm (R1) male thread and approx. 42 mm (R1¼) female thread

Technical Data

- | | |
|---------------------------|------------------------------------|
| ■ Mains: | 230 V ~ 50 Hz |
| ■ Power: | 1,150 W |
| ■ Delivery capacity max.: | 5,500 l/h |
| ■ Delivery height max.: | 48 m |
| ■ Delivery pressure max.: | 4.8 bar |
| ■ Suction height max.: | 8 m |
| ■ Suction connection: | approx. 33.3 mm (R1) female thread |
| ■ Pressure connection: | approx. 42 mm (R1¼) male thread |
| ■ Water temperature: | up to 35 °C |
| ■ Extra long power cord: | 5 m |
| ■ Product weight: | 12.4 kg |

Logistic Data

- | | |
|-----------------------|--------------------|
| ■ Net weight: | 12.4 kg |
| ■ Gross weight: | 14.4 kg |
| ■ Packing dimensions: | 460 x 340 x 425 mm |
| ■ Bar code: | 4006825 589672 |
| ■ Sales unit: | 1 pc |

