



# NPSP 18500 Dirt Water Pump

Art.-No. 41.706.73

The rugged and powerful dirt water pump for moving waste water, it takes foreign particles up to Ø 35 mm in size. In addition to its typical use in excavation pits, this pump is particularly suitable for emptying garden ponds and swimming pools. Thanks to its continuously adjustable float switch the pump is an indispensable tool during floods and in case of burst pipes.

## Features

- Carrying handle (1) with integrated cable reel
- Pump housing made of stainless steel (2)
- Continuously adjustable float switch (3)
- Intake housing and motor housing made of stainless steel (4)
- Universal connection for 25 mm (1") and 32 mm (1¼") male thread hose connection as well as ca. 33.3 mm (G1) male thread (5)
- 90 °angel bracket with ca. 47.8 mm (G1½) x ca. 47.8 mm (G1½) male thread (3)
- Rope 10 meter (6)

## Technical Data

- |                               |                            |
|-------------------------------|----------------------------|
| ■ Mains:                      | 220 - 240 V ~ 50 Hz        |
| ■ Power:                      | 800 watt                   |
| ■ Delivery capacity max.:     | 18,500 l/h                 |
| ■ Delivery height max.:       | 8 m                        |
| ■ Immersion depth max.:       | 5 m                        |
| ■ Water temperature max.:     | up to 35 °C                |
| ■ Hose connection:            | approx. 47.8 mm (G 1 ½) IG |
| ■ Foreign particle size max.: | Ø 35 mm                    |
| ■ Mains cable length:         | 15 m                       |
| ■ Product weight:             | 7.9 kg                     |

## Logistic Data

- |                       |                    |
|-----------------------|--------------------|
| ■ Net weight:         | 8 kg               |
| ■ Gross weight:       | 8.5 kg             |
| ■ Packing dimensions: | 240 x 200 x 455 mm |
| ■ Bar code:           | 4006825 588699     |
| ■ Sales unit:         | 1 pc               |

