

## Split Air Conditioner SKA 5003 C+H

Art.-No.: 23.655.30

Bar code: 4006825542011

Sales unit: 1 pc

Split Air Conditioner for **cooling and heating** with a **cooling capacity of 5,000 watts** and a **heating capacity of 5,300 watts** – for wall installation. **Automatic dehumidification.**

**Complete with remote controlled transmitter** and 4 m cooling agent connecting tubes (max. 10 m possible) with flexible insulation; **Time programming device for ON/OFF.** The outdoor unit can be used by temperatures from -7°C up to 43°C.

The unit consists of 2 parts, an outdoor part and one for indoors, in order to allow quick cooling and warrant an optimal noise level. The Air Conditioner is ideal for large rooms until approx. 150 m<sup>3</sup>.

Due to the possibility of heating operation, the air conditioner can additionally also be used as „interseasonal heating“.

Adjustment of the fan in 3 velocities with a maximum speed of 800 m<sup>3</sup>/h.

With the **automatic dehumidification** the units evaporates from its surrounding **1.7 l/h** excess humidity.

**Timer for programme settings, Automatic- and night functions.** All functions can be set with the **remote controlled transmitter.** Supplied with LCD indicator. Motorized ventilation lamella in the indoor unit.

### Unit dimensions / Weight:

Indoor unit (WxDxH): 940x175x275 mm / 10 kg

Outdoor unit (BxTxH): 760x285x590 mm / 42 kg

### Packing dimensions / Weight:

Indoor unit (BxTxH): 1030x285x365 mm / 13 kg

Outdoor unit (BxTxH): 887x385x655 mm / 45 kg

### Features:

- LED-Display (1)
- Air suction grid (2)
- Air escape plate fin (3)
- Fan (4)
- Remote control (5)
- 4 m refrigerant connection pipes (6)

### Technical Data:

- Coolant:	R410A
- Energy- Efficiency- Class:	C
- EER / COP:	2.94 / 3.02
- Energy consumption at cooling:	850 kWh/year
- Cooling capacity max.:	5,000 W / 17,000 BTU/h
- Heating capacity max.:	5,300 W / 18,000 BTU/h
- Air throughput max.:	800 m <sup>3</sup> /h
- Capacity of humidity reduction max.:	1.7 l. /h
- Mains:	220 – 240 V ~ 50 Hz
- Refrigerant quantity:	1,380 g for 4 m pipe
- Noise level:	Indoors: ≤ 45 dB (A) Outdoors: ≤ 58 dB (A)

Characteristics according to EN 14511

