



## Submersible Pump PVSP 75/150

Art.-No.: **41.705.89**

Bar code: **4006825534856**

Sales unit: **4 pcs**

Powerful and robust submersible pump to empty garden ponds, flooded basements and construction sites. It takes foreign particles up to Ø 35 mm in size. The pump is equipped with a float switch for automatic ON/OFF operation for a varying water level.

High quality standard at materials and constructional design, e. g. a stainless high-grade steel drive shaft warrants a maintenance-free operation and durable application.

### Features:

- Carrying handle (1)
- Float switch (2)
- 90 ° angle bracket with 1 ½" x 1 ½" male thread (3)
- Universal connection for 1" and 5/4" hoses as well as 1" male thread (4)

### Technical data:

- Mains: 230 V ~ 50 Hz
- Power: 750 watts
- Delivery capacity max.: 15,000 l/h
- Delivery height max.: 8 m
- Immersion depth max.: 8 m
- Water temperature max.: 35°C
- Hose connection: 1 ½ " female thread
- Foreign particles size: Ø 35 mm
- Mains cable: 10 m H05RN-F
- ON function: approx. 50 cm
- OFF function: approx. 5 cm
- Suction height: approx. 40 mm
- Weight: 6.1 kg
- Packing dimensions: 220 x 160 x 360 mm



### Performance data:

Delivery height:	Delivery capacity:
2 m	approx. 13,000 l/h
4 m	approx. 9,800 l/h
6 m	approx. 5,300 l/h

### As special accessory available:

Drainage hose 10 m / 1"(material: PVC) **Art.-No.: 41.737.11**  
**Bar code: 4006825414707**



Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved

File: S:\shared-pool\Product-Dokumentation\T-Produktbeschreibung\30\_n0t\Originale\_Englisch\_PA04\4170589\_01016.doc

Erstelldatum / create date: 08.12.2006 09:51:00

Aktualisiert / up dated: 18.12.2006