



NPFP 15000

Submersible pump


Flat immersion

Art.-No. 41.706.65

This pump is ideal for emptying flooded basements, tanks and containers, etc. The integrated float switch controls the ON/OFF functions of the pump. For clearing shallow fluid levels (up to 2 mm) the float switch can be fastened in continuous operation position.

Features

- Change-over switch for automatic and continuous operation
- Integrated float switch
- Carrying handle
- Universal connection for 25 mm (1") and 32 mm (1¼") male thread hose connection as well as ca. 33.3 mm (G1) male thread
- Integrated cable reel



Technical Data

- | | |
|-------------------------------|--|
| ■ Mains: | 230 V ~ 50 Hz |
| ■ Power: | 750 watts |
| ■ Delivery capacity max.: | 15,000 l/h |
| ■ Delivery height max.: | 10 m |
| ■ Delivery pressure: | 1 bar |
| ■ Immersion depth max.: | 5 m |
| ■ Water temperature max.: | 35 °C |
| ■ foreign particle size max.: | 5 mm |
| ■ Hose connection: | approx. 42 mm
(G 1¼) AG male thread |
| ■ Immersion min.: | 2 mm |
| ■ Main cable: | 15 m |
| ■ Product weight: | 6.9 kg |

Logistic Data

- | | |
|-----------------------|--------------------|
| ■ Net weight: | 7.0 kg |
| ■ Gross weight: | 7.5 kg |
| ■ Packing dimensions: | 240 x 220 x 380 mm |
| ■ Bar code: | 4006825 594027 |
| ■ Sales unit: | 1 pc |

