



Einhell

ACCESSORY



PXC-Starter-Kit

5,2Ah & 4A Fastcharger

Item No.: 4512114

Ident No.: 21010

Bar Code: 4006825656787

The Einhell 18V 5.2 Ah PXC Starter Kit is the ideal basis for building up the PXC range in your home. A single rechargeable battery and charger for all tools saves significant costs of buying, and universal use also helps protect the environment and provides flexibility at the same time. The ABS process-controlled active battery management system ensures max. safety, optimum tool performance, maximum operating time and a maximum service life. The high-quality rechargeable battery resists the memory effect and self-discharge. The high-speed battery charger makes short charging times, optimum charging and max. safety possible thanks to intelligent charging management. There is a refresh mode for reactivating exhaustively discharged batteries.



Features & Benefits

- Universal usability for all Power X-Change rechargeable devices:
- Saving money, protecting the environment, and flexibility
- Battery features:
- PLUS-technology: extra power for intensive operation
- The ABS process-controlled battery management system stands for
- max. safety, optimum performance, operating time + lifetime
- Freedom of cordless operation: No tangled cables and free working
- High-quality Li-Ion cells means no memory effect,
- low self-discharge and high, constant power
- Current charge level indicated by 3-stage LED display
- Impact protection and good grip thanks to rubber-coated housing
- Trough handle for easy removal
- Housing protected against dust, corrosion and mechanical damage
- Suitable for TWIN-PACK use in power demanding 36V applications
- Charger features:
- 4-Amp fast-charging technology ensures shorter charging times
- Permanent battery monitoring for optimum charging
- Refresh mode allows deeply discharged batteries to be reactivated
- Maximum safety due to intelligent charge management
- Current information on 6-stage status LED display
- Integrated suspension eyelets for user-friendly wall-mounting



Technical Data

- Mains supply charger	200-250 V 50-60 Hz
- Voltage output charger	20 V
- Charging time	80min
- Voltage	18 V
- Battery capacity	5200 mAh
- Max. power	1260 W
- Amount of batteries	1 Pieces



Logistic Data

- Product weight (kg)	0.39
- Gross weight (kg)	1.45
- Dimensions single packaging	216 x 87 x 180 mm
- Pieces per export carton	9 Pieces
- Gross weight of export carton	15 kg
- Dimensions export carton	435 x 240 x 275 mm
- Container quantity (20"/40"/40"HC)	8460 0 0