



Submersible pressure pump

**GE-PP 1050 N-A** 

Item No.: 4171435

Ident No.: 21014

Bar Code: 4006825679892

The Einhell submersible pressure pump GE-PP 1050 N-A with automatic operation can pump clear water from cisterns, boreholes, wells and water reservoirs. With a maximum discharge head of 45 m, immersion depths of up to 12 m are possible. The 1050 watts of power enable a maximum flow rate of 6000 litres per hour in continuous operation. The pump is equipped with protection against dry-running and an overload switch, as well as a robust pressure connection with stainless-steel insert and high-quality mechanical seals for a long service life. 4 pump impellers ensure a high delivery pressure. The housing is made from stainless steel. The 33.3 mm (1" female thread) hose connection on the upper side of the pump is easily accessible

## Features & Benefits

- Automatic operation automatically starts/stops the pump
- Integrated dry-run protection
- 4-stage impeller system for high delivery pressure
- High discharge pressure for irrigation, e.g. with sprinklers
- Pump and motor housing made from rustproof stainless-steel
- Integrated non-return valve
- High-quality mechanical seal for long service life
- Easy-access hose connection on top of the pump
- High immersion depth thanks to long power cable
- Lifting eyes for attaching the lowering cable
- Robust pressure connection with stainless steel insert
- Practical carrying handle for easy transport

## **Technical Data**

220-240 V | 50 Hz - Mains supply - Power 1050 W - Max. delivery capacity 6000 L/h - Max. delivery height 45 m - Max. immersion depth 12 m 35 °C - Max. water temperature - Max. size of foreign particles 0 mm

- Hose connection 33,3mm (R1 IG) - Power cord 15 m | H07RN-F

## **Logistic Data**

- Product weight 8.5 kg - Gross weight single packaging 11.3 kg

- Dimensions single packaging 260 x 225 x 570 mm

- Pieces per export carton 1 Pieces - Gross weight export carton 11.3 kg

- Dimensions export carton 530 x 260 x 215 mm - Container quantity (20"/40"/40"HC) 952 | 1920 | 2168

















