

## Air Conditioner MKA 2001 M

Art.-No.: 23.601.15

Bar code: 4006825535778

Sales unit: 1 pc

Mobile and compact air conditioner provides an ideal room climate. Cooling and dehumidifying in one unit. The unit is completely assembled and ready for service after the exhaust hose has been connected. The operating levels Cooling and Blowing can be set with mechanical rotation switch and also the air conditioner can be switched off. This model is suitable for rooms of max. 55 m<sup>3</sup> volume.

### Features:

- Horizontal mechanically adjustable air discharge lamellas (1)
- Large rotation switch (2)
- 4 pcs castors (3)
- Recessed grip (4)
- Exhaust air hose (length max. 120 cm) with window adapter (5)
- Air-intake filter
- Condensate return into the cooling operation – no condensate tank emptying necessary
- Integrated condensation water tank (approx. 1.2 litre capacity)

### Technical data:

- Mains: 230 V ~ 50 Hz
- Protection class: IP 21
- Free of FCKW (R407C)
- Quantity of coolant: 400 g
- Energy-Efficiency-Class: D
- EER / COP: 2.16 / -
- Cooling capacity: 1,900 watts / 6,500 BTU/h
- Energy consumption by cooling: 440 kWh per year
- Air circulation max.: 300 m<sup>3</sup>/h
- working operating room temperature: 18°C up to 30°C
- Housing dimensions (B x T x H): 440 x 330 x 790 mm
- Packaging dimensions (B x T x H): 500 x 400 x 875 mm
- Unit Weight: approx. 22 kg
- Weight complete: approx. 26 kg

### Characteristics according to EN 14511

### Functions:

- Display with LED
- Air conditioner off
- Blower slowly / fast
- Blower with cooling slowly / fast

### LED for:

- Power
- Run
- Water tank "full"

