



Dirt water pump NSP 75

Art.-No.: **41.705.90**

Bar code: **4006825542387**

Sales unit: **4 pcs**

Powerful and robust submersible pump to empty garden ponds, flooded basements and construction sites. It takes foreign particles up to Ø 35 mm in size. The pump is equipped with a float switch for automatic ON/OFF operation for a varying water level.

High quality standard at materials and constructional design, e. g. a stainless high-grade steel drive shaft warrants a maintenance-free operation and durable application.

Features:

- Carrying handle (1)
- Float switch (2)
- 90 ° angle bracket with 1 ½" x 1 ½" male thread (3)
- Universal connection for 1" and 5/4" hose connection as well as 1" male thread (4)

Technical data:

- Mains: 230 V ~ 50 Hz
- Power: 750 watts
- Delivery capacity max.: 15,000 l/h
- Delivery height max.: 8 m
- Immersion depth max.: 8 m
- Water temperature max.: 35°C
- Hose connection: 1 ½" female thread
- Foreign particles size: Ø 35 mm
- Mains cable: 10 m H05RN-F
- „ON“-Function: approx. 50 cm
- „OFF“-Function: approx. 5 cm
- Minimum immersion: approx. 40 mm
- Weight: 6.1 kg
- Packing dimensions: 220 x 160 x 360 mm

Performance data:

| | |
|------------------|--------------------|
| Delivery height: | Delivery capacity: |
| 2 m | max. 13,000 l/h |
| 4 m | max. 9,800 l/h |
| 6 m | max. 5,300 l/h |

