

Split-Air Conditioner SKA 5000 C + H

Art.-No.: 23.653.62

Bar-Code: 4006825234763

Sales unit: 1 pc

Air conditioner for **cooling and heating** for wall installation.

Automatic de-humidifying of air in a room

Complete with remote controlled transmitter and 4 m connecting copper tubes with flexible insulation (max. 15 m possibly)

Time programming device for ON/OFF.

Easy installation of the air conditioner with a cooling capacity of **4.500 watts/ 16.000 BTU** and a heating capacity of **4.800 watts/ 17.000 BTU/h**. Ideal for large rooms until approx. 150 m³.

The unit consists of 2 parts, an outdoor part and one for indoors, in order to allow quick cooling and warrant an optimal noise level.

3 setting of fan speed with a maximum speed of 750.m³/h.

With the **automatic de-humidification** the units evaporates from its surrounding approx **1.5 l/h** of excess humidity.

Timer for programme settings, Automatic- and night functions.c

All functions can be set with the **remote controlled transmitter**. Supplied with LCD indicator. Motorized ventilation lamella in the indoor unit.

Dimensions:

Indoor unit (WxHxD): 1000 x 320 x 198 mm

Outdoor unit (WxHxD): 850 x 610 x 290 mm

Weight:

Indoor unit: 15 kg

Outdoor unit: 43 kg

Weight total gross: 64 kg

Packing dimensions 1100 x 530 x 1030 mm

(WxDxH):

Features:

- Air suction grid (1)
- LED-display (2)
- Remote control (3)
- Air escape plate fin (4)
- Fan (5)

Technical data:

- Free of FCKW (R407C)
- Energy-Efficiency-Class: C
- EER / COP: 2,85 / 3,24
- Energy consumption when cooling: 890 kWh per year
- Cooling capacity: 4.500 watts / 16.000 BTU/h
- Heating capacity: 4.800 watts / 17.000 BTU/h
- Air throughput: 750 m³/h
- Capacity of humidity reduction: 1.5 l/h
- Mains: 230 V ~ 50 Hz
- Power during cooling: 1690 watts
- Power during heating: 1660 watts
- Refrigerant quantity: approx. 1300 g for 4 m of tube (for each further meter 20 g encloses)
- Noise level: Indoors: 43 dB(A)
Outdoors: 56 dB(A)

