

Information requirements for electric local space heaters

Model identifier(s): CH 2000/1

| Item | Symbol | Value | Unit | Item | Unit |
|--|---|-------|------|---|------|
| Heat output | | | | Type of heat input, for electric storage local space heaters only (select one) | |
| Nominal heat output | P_{nom} | 2,0 | kW | manual heat charge control, with integrated thermostat | - |
| Minimum heat output (indicative) | P_{min} | 0,8 | kW | manual heat charge control with room and/or outdoor temperature feedback | - |
| Maximum continuous heat output | $P_{max,c}$ | 2,0 | kW | electronic heat charge control with room and/or outdoor temperature feedback | - |
| Auxiliary electricity consumption | | | | fan assisted heat output | |
| At nominal heat output | $e_{l,max}$ | 0,000 | kW | Type of heat output/room temperature control (select one) | |
| At minimum heat output | $e_{l,min}$ | 0,000 | kW | single stage heat output and no room temperature control | No |
| In standby mode | $e_{l,SB}$ | 0,000 | kW | Two or more manual stages, no room temperature control | No |
| | | | | with mechanic thermostat room temperature control | Yes |
| | | | | with electronic room temperature control | No |
| | | | | electronic room temperature control plus day timer | No |
| | | | | electronic room temperature control plus week timer | No |
| | | | | Other control options (multiple selections possible) | |
| | | | | room temperature control, with presence detection | No |
| | | | | room temperature control, with open window detection | No |
| | | | | with distance control option | No |
| | | | | with adaptive start control | No |
| | | | | with working time limitation | No |
| | | | | with black bulb sensor | No |
| Contact details | ISC GmbH, Eschenstr. 6, D-94405 Landau/Isar | | | | |