



NPTP 6000

Submersible pressure pump

Art.-No. 41.709.62

The robust submersible pressure pump is most suitable for delivery of clear water from reservoir, well and shafts. The deep well pump is also able to pump the water up from large depths and because of the multi-stage rotor-system the water can be transfer with much pressure. The integrated motor-thermo protection protects the pump against overloading. The vertical pressure line connection consists of stainless steel.

Features

- Hose connection (1) for approx. 25.4 mm (1")
- 2 ring bolts (2)
- Float switch (3)
- Pump housing consist of rust-free stainless steel (4)
- 3 high quality plastic pump wheels
- High quality floating ring seal
- Rope 10 meter (5)



Technical Data

- | | |
|---------------------------|------------------------------------|
| ■ Mains: | 220 - 240 V ~ 50 Hz |
| ■ Power: | 800 W |
| ■ Delivery quantity max.: | 6,000 l/h |
| ■ Delivery height max.: | 32 m |
| ■ Immersion depth max.: | 8 m |
| ■ Water temperature max.: | 35 °C |
| ■ Hose connection: | approx. 33.3 mm (G1) female thread |
| ■ Foreign particle: | up to 2.5 mm |
| ■ Mains cable: | 15 m |
| ■ Protection class: | I |
| ■ Plastic pump wheels: | 3 pcs |
| ■ Switch point ON: | 50 cm |
| ■ Switch point OFF: | 5 cm |
| ■ Product weight: | 8.9 kg |

Logistic Data

- | | |
|-----------------------|--------------------|
| ■ Net weight: | 9.4 kg |
| ■ Gross weight: | 9.8 kg |
| ■ Packing dimensions: | 245 x 190 x 455 mm |
| ■ Bar code: | 4006825 588606 |
| ■ Sales unit: | 1 pc |

