

Cross-cut and mitre saw with upper table KGST 210/1

Art.-No.: **43.003.10**

bar code: 4006825430806

Sales unit: 1 pc

With model KGST 210/1 one can cut wood, plastics, aluminium, brass and copper precisely and effortlessly. This unit is ideal for length cutting, trimming of floor- and wall panelling boards, picture frames as well as door- and window sills.

- Continuously adjustable turnable from -45° up to $+45^\circ$ (1)
- Tilting motor head from 0° to 45° to the left (2)
- Continuously adjustable table height from 0 to 33 mm (3)
- Guide fence adjustable in parallel- and square position from -30° to $+30^\circ$ (4)
- Work-piece support (5)

Technical data:

Mains: 230V ~ 50Hz
Power: 1200 watts
Idle speed: n_0 : 4600 min^{-1}
Carbide tipp. saw bl.: $\varnothing 210 \times \varnothing 30 \times 2,8 \text{ mm}$
No of teeth: 24
Base plate size: 400 x 285 mm
Tilting area: $-45^\circ / 0^\circ / +45^\circ$

Weight: 13,2 kg
Packing dimensions: 480x450x330 mm

Operating as a cross-cut saw:

Angle cutting range: 0° to 45°
Saw bed support: 390 x 140 mm
Cutting width at 90° : 120 x 55 mm
Cutting width at tilting table 45° : 65 x 55 mm
Cutting width at 2x 45° : 40 x 23 mm
(double angle cutting range)

Operating as a table saw:

Support cutting table: 360 x 250 mm
Cutting height: 0 - 33 mm
Parallel- and angle fence: -30° to $+30^\circ$



As accessory available:

Saw blade
 $\varnothing 210 \times 30 \times 2,8 \text{ mm}$, 24 teeth

Art.-No.: **45.020.48**

bar code: 4006825426004