

Table Saw TK 1500 UV

Art.-No.: 43.406.51

Bar code: 4006825506587

Sales Unit: 1 pcs

The table saw can be used in several operations. The simple-installable extension table guarantees a wide work surface, whereby the length support can be used in total width. The TK 1500 UV is designed for multi-purpose application: ripping and crosscuts of lumber, chipboard, plywood, multiplex board and veneered sheets. Its compact construction, practical transport handling and its power make ideally suitable for us in construction sites and for interior decorating work. The saw can be tilted up to 45° for mitre cuts. The cross cut fence can be left or right of the saw blade and is equipped for 2 different heights. It can of course be set on either side to $-+45^{\circ}$. The splitting wedge can be taken out for covered cuts.

Features:

- Number scale with loupe (1)
- Push stick with clamp (2)
- Cross fence with angle scale (3)
- Extension table and length extension table of powder coated sheet steel (4)
- Anodizing table surface for better anti-friction property (5)
- Saw blade protection with suction hose (6)
- Parallel stop with aluminium guide (7)
- Saw blade angle adjustment (8)
- Saw blade height adjustment (9)
- Carbide tipped saw blade
- Powder-coated housing

Technical data:

 $\begin{array}{lll} \mbox{- Power:} & 1500 \mbox{ watts, $S6.40 \%$} \\ \mbox{- Idle speed:} & 5.700 \mbox{ min}^{-1} \\ \mbox{- Mains:} & 230 \mbox{ V} \sim 50 \mbox{ Hz} \\ \mbox{- Cutting height at} & 90^{\circ}: 73 \mbox{ mm} \\ \mbox{45 }^{\circ}: 53 \mbox{ mm} \\ \end{array}$

- Saw blade: Ø 250 x Ø30 x 2,4 mm, 24 teeth

- Motor rotation range: $0-45^{\circ}$ - Cross fence tilt able: $2 \times 0-45^{\circ}$

- Machine size without additional table(W x L x H): 640 x 440 x 1100 mm - Table size: 595 x 440 mm

- Table width extension left/right: 595 x 250 mm
- Table length extention back side: 440 x 320 mm
- Height without undercarriage: 310 mm
- Working height with undercarriage: 900 mm

- Weight: 33,5 kg

- Packing dimensions: 720 x 590 x 360 mm

