

Agreeable climate in modern design!


**Einhell**®

**NEW GENERATION**



Mobile and compact air conditioner, which provides a comfortable indoor climate. Cooling and dehumidifying in one unit. The unit is completely assembled and ready for service after the exhaust hose has been connected.

With soft keys all operating levels can be set and also the air conditioner can be switched on/off. The thermostat regulation provides a well-balanced indoor climate. This model is suitable for rooms of max.80 m<sup>3</sup>.



## NMK 2700 E Portable Air Conditioner

### Logistic Information:

<b>Type:</b>	<b>NMK 2700 E</b>	<b>Sales unit:</b>	1 pc
<b>Art.-No.:</b>	23.602.05	<b>20``:</b>	92 pcs
<b>Ident-No.:</b>	01038	<b>40``:</b>	196 pcs
<b>Bar Code</b>	4006825 534009	<b>40`` HC:</b>	292 pcs
<b>Packaging:</b>	695 x 395 x 887 mm	<b>Weight:</b>	35.5 kgs (gross)



Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery. Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved.

File: S:\shared-pool\Product-Dokumentation\T-Produktbeschreibung\30\_n0t\Originale\_Englisch\_PA04\2360205\_01038.doc

Erstelldatum/create date: 13.11.2008 11:03:00Aktualisiert/up dated: 13.07.2010

# Agreeable climate in modern design!

# Einhell®

## NEW GENERATION

Large, foldable display  
with backlight



Carrying  
handle



Mains cable storage  
space with coverage



Air discharge opening lamellas  
are adjustable mechanically in  
horizontal position



4 pcs castors



Remote control

### Functions:

- LCD-Display, with backlight
- Target – temperature attitude: +18°C up to +30°C
- Fan speed: 3-settings
- Operating level section (Mode): Cooling, Dehumidifying, Ventilation
- „Swing“ - Function
- Temperature display reversible °C / °F
- Input delay: 0.5 to 24 h
- Power-on time: 0.5 to 24 h, Continuous operation
- Unit ON-OFF

### LCD-Display for:

- Actual temperature
- Target temperature
- Timer on
- Fan speed
- Cooling, Dehumidifying, Ventilation
- Swing - Function on
- Condensation water tank full

### Features:

- Large, foldable control panel
- Air suction filter with active carbon filter
- Air discharge opening lamellas are adjustable mechanically in horizontal position
- Condensate return during the cooling operation - no condensate box deflation necessary
- Integrated condensation box (approx. 1.2 litre volume)
- Air dehumidifier - function (constant dehydration over condensation hose)
- Mains cable storage space with coverage
- 4 pcs castors
- Remote control

### Technical Data:

- Coolant: R407C
- Energy-Efficiency-Class: B
- EER / COP: 2.45 / -
- Energy consumption at cooling: 530 kWh/year
- Mains: 230 V ~ 50 Hz
- Cooling capacity: 2,600 W / 9,000 BTU/h
- Air circulation max.: 440 m³/h
- Exhausted room humidity max.(30°C / 80% RH): aprox. 64 l/day
- Quantity of coolant: 500 g
- Noise level: ≤50dB (A)
- Weight (net): 32 kg
- Characteristics of: EN 14511

### Logistic Information:

<b>Type:</b>	<b>NMK 2700 E</b>	<b>Tool:</b>	<b>Portable Air Conditioner</b>
<b>Art.-No.:</b>	23.602.05	<b>Sales unit:</b>	1 pc
<b>Ident-No.:</b>	01038	<b>20``:</b>	92 pcs
<b>Bar Code</b>	4006825 534009	<b>40``:</b>	196 pcs
<b>Packaging:</b>	695 x 395 x 887 mm	<b>40``HC:</b>	292 pcs
		<b>Weight:</b>	35,5 kgs (gross)

