



Submersible Pump NTP 25

Art.-No.: 41.702.89

Bar code: 4006825511888

Sales unit: 4 pcs

Ideal to empty flooded basements, tanks, containers etc. is only approx. 4 kg heavy submersible pump. The installed float switch automatically switches the pump ON and OFF.

High quality by the material and constructional execution, e. g. the stainless high-grade steel drive shaft, warrants an almost maintenance-free operation and a long life span. The complete housing is made of an impact resistant plastic.

Technical data:

- Mains:	230 V ~ 50 Hz
- Power:	250 watts
- Delivery capacity max.:	6200 l/h
- Delivery height max.:	5.5 m
- Immersion depth max.:	5 m
- Water temperature:	up to 35°C
- Foreign particles size max.:	Ø 3 mm
- Mains cable:	10 m H05RN-F
- ON function:	ca. 50 cm
- OFF function:	ca. 5 cm
- Hose connection:	1 ¼" female thread
- Minimum immersion:	8 mm
- Weight:	4.3 kg
- Packing Dimensions:	240 x 175 x 310 mm

Features:

- Carrying handle (1)
- Universal connection for 1" and 1 ¼" hose connection as well as 1" male thread (2)
- 90 ° angle bracket with 1 ¼" x 1 ¼" male thread (3)
- Float switch (4)

Performance data:

Delivery height:	Delivery capacity:
1 m	max.: 4800 l/h
2 m	max.: 3600 l/h
3 m	max.: 2400 l/h
4 m	max.: 1500 l/h



As special accessory available:

PVC-Drainage hose 10 m / 1"

Art.-No.: 41.737.11
Bar code: 4006825414707



Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved

File: S:\shared-pool\Product-Dokumentation\T-Produktbeschreibung\30_n0t\Originale_Englisch_PA04\4170289_01026.doc

Erstelldatum / create date: 07.04.2006 11:35:00

Aktualisiert / up dated: 07.04.2006